

### 空气绝缘开关柜用互感器

6-35kV 户内电流互感器

户内 单相 环氧树脂浇注式

INDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

#### 技术参数 Technical data

○ 产品性能符合标准：GB/T20840.1、2 和 IEC61869-1、2

The current transformers are in accordance with GB/T20840.1、2 and IEC61869-1、2 standards

○ 额定绝缘水平：12/42/75kV

○ 额定二次电流：5A 或 1A

Rated insulation level 12/42/75kV

Rated secondary current 5A or 1A

○ 额定频率：50Hz 或 60Hz

○ 环境温度：-5℃ ~+40℃

Rated frequency 50Hz or 60Hz

Ambient temperature -5℃ ~+40℃



额定一次电流 Rated primary current (A)	一秒热稳定电流 1s thermal current (kA)	动稳定电流 dynamic current (kA)	准确级组合 Accuracy classes combination	额定二次输出 (VA) Rated secondary output (VA)					表面爬电距离 Surface creepage distance(mm)	重量 Weight(kg)
				0.2S	0.5S	0.2	0.5	10P10		
5-40	$90 I_n \times 10^{-3}$	$220 I_n \times 10^{-3}$	0.2(S)/0.2(S) 0.2(S)/0.5(S) 0.2(S)/10P 0.5(S)/10P	10	10	10	15	15	255	15
50-400	$100 I_n \times 10^{-3}$	$250 I_n \times 10^{-3}$								
500	50	100								
600	56	110								
800	75	110								
1000	80	130								

#### 外形及安装尺寸 Overall dimension drawing

