

## 空气绝缘开关柜用互感器

6-35kV 户内电流互感器

户内 单相 环氧树脂浇注式

INDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

### 技术参数 Technical data

○ 产品性能符合标准：GB/T20840.1、2 和 IEC61869-1、2  
The current transformers are in accordance with GB/T20840.1、2 and IEC61869-1、2 standards

○ 额定绝缘水平：12/42/75kV      ○ 额定二次电流：5A 或 1A  
Rated insulation level 12/42/75kV      Rated secondary current 5A or 1A

○ 额定频率：50Hz 或 60Hz      ○ 环境温度：-5℃ ~+40℃  
Rated frequency 50Hz or 60Hz      Ambient temperature -5℃ ~+40℃



额定一次电流 Rated primary current (A)	一秒热稳定电 thermal current (kA)	动稳定电流 Rated primary current (kA)	准确级组合 Accuracy classes combination	额定二次输出 Rated primary current (VA)				表面爬电距离 Surface creepage distance(mm)	重量 Weight(kg)
				0.2(S)	0.2	0.5	5P10		
5	0.6	1.5	0.2(S)/0.2(S) 0.2(S)/0.5(S) 0.5(S)/0.5(S) 0.2(S)/5P10 0.5(S)/5P10	10	10	15	15	210	20
10	1.1	2.75							
15	1.7	4.25							
20、25	2.7	6.75							
30	4	10							
40	5	12.5							
50	9	22.5							
75	13.5	33							
100	18	45							
150	27	63							
220、250	63	100							23
300、400									
500、800									
1000、1250									

### 外形及安装尺寸 Overall dimension drawing

