

空气绝缘开关柜用互感器

6-35kV 户内电流互感器

户内 单相 环氧树脂浇注式

INDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

技术参数 Technical data

- 产品性能符合标准：GB/T20840.1、2 和 IEC61869-1、2
The current transformers are in accordance with GB/T20840.1、2 and IEC61869-1、2 standards
- 额定绝缘水平：40.5/95/185kV ○ 额定二次电流：5A 或 1A
Rated insulation level 40.5/95/185kV Rated secondary current 5A or 1A
- 额定频率：50Hz 或 60Hz ○ 环境温度：-5℃ ~+40℃
Rated frequency 50Hz or 60Hz Ambient temperature -5℃ ~+40℃



额定一次电流 Rated primary current(A)	短时热电流 Short-time thermal current(kA/S)		动稳定电流 (kA) Raten dynamic current(kA)	准确级组合 Accuracy classes combination	额定二次输出 Rated secondary output(VA)					表面爬电距离 Surface creepage distance(mm)	重量 Weight (kg)
	kA	S			0.2(S) 0.5(S)	0.5	5P20	5P25	5P30		
20	4	1	10	0.2/0.5 0.2/5P 0.5/5P	10	15	60	50	15	820	60
30-40	4	2	10								
50	12	1	30								
75	16	1	40								
100-150	25	1	63								
200-300	31.5	1	80								
400-600	31.5	2	80								
800-1600	31.5	4	130								
2000-3150											

注：如果用户要求的参数超出上表范围，可与我公司协商后确定。
Note: If the required parameter is beyond the above range, it can be discussed and confirmed with us.

外形及安装尺寸 Overall dimension drawing

