

空气绝缘开关柜用互感器

3-40.5kV 户内电压互感器

户内 单相 环氧树脂浇注式

INDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

技术参数 Technical data

○ 产品性能符合标准：GB/T20840.1、3 和 IEC61869-1、3
The voltage transformers are in accordance with GB/T20840.1、3 and IEC61869-1、3 standards

○ 额定频率：50Hz 或 60Hz
Rated frequency 50Hz or 60Hz

○ 环境温度：-5℃ ~+40℃
Ambient temperature -5℃ ~+40℃



电压互感器

型号 Type	额定电压比 (V) Rated voltage ratio	准确度或准确度组合 额定二次输出 (VA) Accuracy class and accuracy class combination rated secondary output	热极限输出 (VA) Limited output	额定绝缘水平 (kV) Rated insulation level	表面爬电距离 (mm) Surface creepage distance	重量 (kg) weight	接线图 Wiring diagram
JDZ-3	3000/100	0.2-20 0.5-30 1-50 3-80	200	3.6/23/40	250	22	图 1-图 2 Figure 1-2
JDZ-6	6000/100	0.2-30 0.5-50 1-80 3-200	400	7.2/32/60			
	6000/220						
JDZ-10	10000/100	0.2-30 0.5-80 1-150 3-300	500	12/42/75	250	22	
	10000/220						
JDZ-3	3000/100/100	0.2/0.2-15/15 0.2/0.5-15/15 0.5/0.5-30-30	150/150	3.6/23/40	250	22	图 3-图 4 Figure 3-4
JDZ-6	6000/100/100	0.2/0.2-20/20 0.2/0.5-20/20 0.5/0.5-30/30	200/200	7.2/32/60			
JDZ-10	10000/100/100	0.2/0.2-20/20 0.2/0.5-20/20 0.5/0.5-50/50	300/300	12/42/75			
	10000/100/220	0.2/3-30/300 0.5/3-80/300	500/500				
JDZJ-3	$\frac{3000}{\sqrt{3}}/\frac{100}{\sqrt{3}}/\frac{100}{3}$	0.2/6P(3P)-20/50 0.5/6P(3P)-30/50 1/6P(3P)-80/50 3/6P(3P)-200/50	200	3.6/23/40	250	22	图 5 Figure 5
JDZJ-6	$\frac{6000}{\sqrt{3}}/\frac{100}{\sqrt{3}}/\frac{100}{3}$	0.2/6P(3P)-20/100 0.5/6P(3P)-50/100 1/6P(3P)-50/100 3/6P(3P)-80/100	400	7.2/32/60			
JDZJ-10	$\frac{10000}{\sqrt{3}}/\frac{100}{\sqrt{3}}/\frac{100}{3}$	0.2/6P(3P)-20/100 0.5/6P(3P)-50/100 1/6P(3P)-80/100 3/6P(3P)-200/100					
	$\frac{10000}{\sqrt{3}}/\frac{100}{\sqrt{3}}/\frac{100}{\sqrt{3}}/\frac{100}{3}$	0.2/0.2/6P(3P)-10/10/100 0.2/0.5/6P(3P)-10/15/100 0.5/0.5/6P(3P)-30/30/100	200/200		图 6 Figure 6		