

LMZK3-10

电流互感器 CURRENT TRANSFORMER

OBC®

环网柜、充气柜用互感器

6-35kV 户内电流互感器

户内 单相 环氧树脂浇注式

INDOOR SINGLE-PHASE EPOXY RESIN CASTING TYPE

技术参数 Technical data

- 产品性能符合标准：GB/T20840.1、2 和 IEC61869-1、2
The current transformers are in accordance with GB/T20840.1、2 and IEC61869-1、2 standards
- 额定二次电流：5A 或 1A ○ 额定频率：50Hz 或 60Hz
Rated secondary current 5A or 1A Rated frequency 50Hz or 60Hz
- 环境温度：-35℃ ~+55℃，日平均温度：≤ 40℃
Ambient temperature：-35℃ ~+55℃，daily average temperature ≤ 40℃
- 工频耐压 3kV, 持续 1min; ○ 海拔高度：≤ 1000 米
Altitude：≤ 1000m



环网柜充气柜用互感器

型号 Type	用途 Purpose	测量电流互感器 Measuring current				保护电流互感器 Protectectice Current transformer		双绕组电流互感器 Double winding current transformer					
	电流比 Ratio	准确级及额定负载 Accuracy class and rated burden				准确级及额定负载 Accuracy class and rated burden		准确级及额定负载 Accuracy class and rated burden					
		0.2	0.5	1	3	10P10	10P5	0.5	1	3	10P10	10P5	
LMZK3-10	75/5				2.5		2.5						
	100/5			2.5		1.5	5		2.5				2.5
	150/5		2.5			2.5	5		2.5				2.5
	200/5		5			3.75	7.5	2.5	3.75				2.5
	300/5	2.5	5			5	10	2.5	5		2.5	5	
	400/5	5	7.5			5	10	5	5		2.5	5	
	500/5	5	7.5			7.5	15	5	5		3.75	7.5	
	600/5	5	10			7.5	15	5	5		3.75	7.5	

外形及安装尺寸 Overall dimension drawing

