

环网柜、充气柜用互感器

6-35kV 电流互感器

户内 三相 环氧树脂浇注式

INDOOR THREE-PHASE EPOXY RESIN CASTING TYPE

技术参数 Technical data

○ 产品性能符合标准：GB/T20840.1、3 和 IEC61869-1、3
The voltage transformers are in accordance with GB/T20840.1、3 and IEC61869-1、3 standards

○ 额定频率：50Hz 或 60Hz
Rated frequency 50Hz or 60Hz

○ 环境温度：-5℃ ~+40℃
Ambient temperature -5℃ ~+40℃



型号 Type	额定电压比 (V) Rated voltage ratio	准确级及准确级组合额定二次输出 (VA) Accuracy class and accuracy class combination rated secondary output	极限输出 (kV) Rated insulation level	额定绝缘水平 (kV) Rated insulation level	一次熔断器 (A) Once fuse	重量 (kg) weight	接线图 Wiring diagram
JSZY16-3R	$\frac{3000}{\sqrt{3}} / \frac{100}{\sqrt{3}} / \frac{100}{3}$	0.2/6P(3P)---3×15/100 0.5/6P(3P)---3×30/100 1/6P(3P)---3×60/100 3/6P(3P)---3×150/100	3×400	3.6/23/40	0.5	92	图5 Figure 5
JSZY16-6R	$\frac{6000}{\sqrt{3}} / \frac{100}{\sqrt{3}} / \frac{100}{3}$			7.2/32/60			
JSZY16-10R	$\frac{10000}{\sqrt{3}} / \frac{100}{\sqrt{3}} / \frac{100}{3}$			12/42/75			
JSZY16-3R	$\frac{3000}{\sqrt{3}} / \frac{100}{\sqrt{3}} / \frac{100}{\sqrt{3}} / \frac{100}{3}$	0.2/0.2/6P (3P) -3×10/3×10/100 0.2/0.5/6P (3P) -3×10/3×15/100 0.2/0.5/6P (3P) -3×30/3×30/100	3×300/3×300	3.6/23/40	0.5	92	图6 Figure 6
JSZY16-6R	$\frac{6000}{\sqrt{3}} / \frac{100}{\sqrt{3}} / \frac{100}{\sqrt{3}} / \frac{100}{3}$			7.2/32/60			
JSZY16-10R	$\frac{10000}{\sqrt{3}} / \frac{100}{\sqrt{3}} / \frac{100}{\sqrt{3}} / \frac{100}{3}$			12/42/75			

外形及安装尺寸 Overall dimension drawing

