

户外用互感器

6-35kV

户外 单相 环氧树脂浇注式

OUTDOORS SINGLE-PHASE EPOXY RESIN CASTING TYPE

技术参数 Technical data

- 产品性能符合标准：GB/T20840.1、2 和 IEC61869-1、2
The current transformers are in accordance with GB/T20840.1、2 and IEC61869-1、2 standards
- 额定绝缘水平：24/65/125kV ○ 额定二次电流：5A 或 1A
Rated insulation level 24/65/125kV Rated secondary current 5A or 1A
- 额定频率：50Hz 或 60Hz ○ 环境温度：-25℃ ~+40℃
Rated frequency 50Hz or 60Hz Ambient temperature -25℃ ~+40℃
- 污秽等级：IV级
Pollution class: class IV



额定一次电流 (A) Rated primary current	短时热电流 (kA/S) Short-time thermal current	额定动稳定电流 (kA) Rated dynamic current	准确级组合 Class combination	准确级及额定输出 (VA) COS φ=0.8 Accuracy class and rated output					表面爬电距离 (mm) Surface creepage distance	重量 (kg) Weight
				0.2(S)	0.5(S)	10P10	10P15	5P20		
30-200	$150I_n \times 10^{-3}$	$375I_n \times 10^{-3}$	0.2(S)/10P 0.5(S)/10P 0.2(S)/0.5(S)/10P	10	10	30	25	20	762	48
300-400	31.5	80								
500-800	63	130								
1000-2000	100	160								

注：如用户要求的参数超出上表范围，可与我公司协商后确定。

Note: If the required parameter is beyond the above range, it can be discussed and confirmed with us.

外形及安装尺寸 Overall dimension drawing

