

组合互感器

6-35kV 户内电流互感器

户外 三相 油浸式

OUTDOORS THREE-PHASE OIL IMMERSED TYPE

技术参数 Technical data

○产品性能符合标准：GB20840.4

The current transformers are in accordance with GB20840.4

○额定绝缘水平：12/42/75kV

○额定频率：50Hz 或 60Hz

insulation level 12/42/75kV

Rated frequency 50Hz or 60Hz

额定电压：6kV、10kV、11kV、33kV、35kV

Rated Voltage: 6kV, 10kV, 11kV, 33kV, 35kV

准确等级：0.5 和 0.2 级、0.5S 和 0.2S 级

Accurate Grade: 0.5 and 0.2, 0.5S and 0.2S

○环境温度：-25℃ ~+40℃

污秽等级：IV 级

Ambient temperature :-25℃ ~+40℃

Pollution class: IV

○额定变化：电压比 3000/100、6000/100、10000/100、11000/100、33000/100、35000/100 电流比 5-300/5(大电流变比可以定做)

Rated Ratio: ratio-voltage 3000/100, 6000/100, 10000/100, 11000/110, 33000/110, 35000/100 ratio=current 5-300/5(high ratio-current can made to order)



型号 Type	额定电压比 Rated voltage Ratio(V)	额定电流比 Rated current Ratio(A)	电压互感器准确等级及额定输出 Voltage transformer Accurate grade and Rated output(VA)		电流互感器准确等级及额定输出 Current transformer Accurate grade and Rated output(VA)		额定绝缘水平 Rated Insulating level(kV)
			0.2 级 Class	0.5 级 Class	0.2(S) 级 Class	0.5(S) 级 Class	
JLS-6 JLS-10 JLS-35	3000/100	5-300/5	20	20	10	10	3.6/25/40
	6000/100	5-300/5	20	20	10	10	7.2/32/60
	11000/110	5-300/5	25	25	10	10	12/42/75
	11000/110	5-300/5	25	25	10	10	12/42/75
	33000/110	5-300/5	50	50	10	10	40.5/95/185
	35000/100	5-300/5	50	50	10	10	40.5/95/182

外形及安装尺寸 Overall dimension drawing

图 1：6kV、10kV、11kV 三相四线油浸式高压电力计量箱（三相三元件）

Diagram 1 :Outline and installing dimension of 6kV, 10kV, 11kV three-phase four-wire-immersed high-voltage electric measuring tank (three-phase three comput)

